



Area Disposal Service, Inc.

Asbestos Wastestream Approval Package

www.pdcarea.com

Profile #: _____

Non-Regulated Asbestos Waste Profile

I. Generator:	
Address: <small>(where waste is being generated)</small>	Mailing Address:
City/State/Zip:	City/State/Zip:
Phone:	Phone:
Generator Contact:	Generator Contact:

II. Contractor/Billing:	
Address:	Mailing Address:
City/State/Zip:	City/State/Zip:
Phone:	Phone:
Contact:	Title:

III. Hauler:	
Address/Phone:	Contact:

IV. Type of Asbestos Material: (Describe):	
Non-friable Category I	Non-Friable Category II
Is this a Regulated Asbestos Containing Material? YES NO	DOT Shipping Description: Non Friable Asbestos, Not-Hazardous by DOT

Removal Methods (describe):

V. Job Type:	Renovation	Demolition	Other (Describe):
Please explain any "NO" responses to the following questions in the space provided below.			
1.) If Renovation or Demolition, has the Agency been notified per 40 CFR 61.145 or applicable State/Local regulations?	YES	NO	
2.) If Demolition, will the asbestos be removed prior to demolition and shipped to an approved facility?	YES	NO	

Explanation:

VI. Waste Volume and Units:	BAGS	DRUMS	OTHER	
VII. Disposal Approval Period Requested:	From:			To:
VIII. Disposal Approval Requested at:	Subtitle D (Non-Hazardous) Landfill?	YES	NO	
	Subtitle C (Hazardous) Landfill?	YES	NO	

IX. Landfill Site Requested:	
-------------------------------------	--

X. Generator Certification: I hereby certify that all information submitted in this and attached documents contain true and accurate descriptions on this asbestos material, and all relevant information regarding known or suspected hazards in the possession of the generator has been disclosed. I further certify that this asbestos material is neither Asbestos Containing Waste Material (ACWM) or Regulated Asbestos Containing Material (RACM) as defined in 40 CFR Part 61, Subpart M.

SIGNATURE	TITLE
PRINTED NAME	DATE
Authorization Granted <input type="checkbox"/>	Signature: _____ Date: _____

Non-friable, non-regulated Asbestos-containing materials (ACM) are any materials containing more than 1 percent asbestos as determined using Polarized Light Microscopy (PLM) that, when dry, cannot be crumbled, pulverized, or reduced to powder by hand pressure. Non-friable ACM includes floor tiles, asbestos cement sheet (transite board), siding shingles, asphalt roofing shingles, laboratory benchtops, and even chalkboards. These materials may become friable with age and under harsh conditions. Non-friable ACM must be carefully examined to determine if the material is in poor condition, that is, if the binding material is losing its integrity, exhibited by peeling, cracking, or crumbling; and is also friable. Also, any non-friable ACM which is damaged to the extent that it has or will become crumbled, pulverized, or reduced to powder due to demolition or renovation activities, is subject to regulation. Both friable and non-friable forms of other asbestos-containing building materials exist. Friable (regulated) materials include asbestos-containing paper (commonly found beneath wooden floors), wallpaper, and joint compound.

Regulated Asbestos Containing Material (RACM) is (a) friable asbestos material, (b) Category I non-friable ACM that has become friable, (c) Category I non-friable ACM that will be or has been subjected to sanding, grinding, cutting, or abrading, or (d) Category II non-friable ACM that has a high probability of becoming or has become crumbled, pulverized, or reduced to powder by the force expected to act on the material in the course of demolition or renovation operations.

The asbestos NESHAP (National Emissions Standards for Hazardous Air Pollutants) defines two categories of non-friable ACM: Category I non-friable ACM (asbestos-containing packings, gaskets, resilient floor covering and asphalt roofing products) and Category II non-friable ACM (any non-friable material not designated in Category I). The Agency requires that, where the asbestos NESHAP is applicable, friable ACM, Category II ACM and non-friable ACM that is likely to become disturbed or damaged so that the material could be crumbled, pulverized, or reduced to powder during a demolition or renovation, be removed from a facility prior to its demolition/renovation. The fibrous or fluffy spray-applied asbestos materials found in many buildings for fireproofing, insulating, soundproofing, or decorative purposes are generally considered friable. Pipe and boiler wrap found in numerous buildings is also considered friable.

Non-friable ACM, such as vinyl-asbestos floor tile, generally emits low levels of airborne fibers unless subjected to burning or to sanding, grinding, cutting, or abrading operations. Other materials, such as asbestos cement sheet and pipe, can emit asbestos fibers if the materials are crumbled, pulverized, or reduced to powder during demolition/renovation activities. Whenever non-friable materials are going to be damaged to the extent that they are crumbled, pulverized, or reduced to powder, they must be handled in accordance with the Asbestos NESHAP.